

f

Real-time Publish-Subscribe (RTPS)

[Return to Glossary](#)

Real-time Publish-Subscribe(RTPS) wireprotocol defines a set of requirements for a wire protocol suitable for the [Data Distribution Service \(DDS\)](#). Primary considerations in the design of the RTPS wire protocol are: [performance](#), configurability (tuning quality-of-service), [fault-tolerance](#) (no single points of failure), extensibility (support new transports), plug-and-play connectivity (automatic discovery), [modularity](#), [scalability](#), and [type safety](#).

RTPS imposes very little requirements on the underlying transport: a connectionless service capable of sending packets [best-effort](#) is sufficient. A connection-oriented protocol can be used but is not required. The mechanisms of the underlying protocol map to the generalized notions of the RTPS [pim](#).

The original [DDSI-RTPS](#) specification defined a [psm](#) built upon the User [udp](#) because of its simplicity, universal [availability](#), best-effort and connectionless capabilities, predictable behavior, scalability, and [multicast](#) support.

However, some DDS systems would benefit from an RTPS PSM built upon the [tcp](#). Among other scenarios, a TCP PSM would be better suited for communication through firewalls, where often UDP traffic is filtered; could leverage existing TCP-based [load-balancing](#) infrastructure; and would allow DDS to be deployed in some applications where governance mandates TCP exclusively. Therefore, the [goal](#) of this [rfp](#) is to meet the requirements set forth by the RTPS PIM with minimum possible overhead using TCP.

Source: [Real-time Publish-Subscribe \(RTPS\)](#)

From:
<https://www.omgwiki.org/ddsf/> - **DDS Foundation Wiki**

Permanent link:
https://www.omgwiki.org/ddsf/doku.php?id=ddsf:public:guidebook:06_append:GLOSSARY:r:rtps&rev=1626291830

Last update: **2021/07/14 15:43**

