

2.3.2.4 Private Networks

[return to Network Access Control](#)

A **private network** limits access to the network to individuals or nodes granted and verified to have permission to participate in joining, leaving, reading, writing, and auditing activities on the network. A participant joins a private network only through an authentic and verified invitation; validation is performed either by the network operator(s) or using a clearly defined set of protocols implemented by the network.¹⁾

Benefits of Private Networks

Enterprise Permissioned²⁾:

The enterprise controls the resources and access to the blockchain, hence private and/or permissioned.

Faster Transactions³⁾:

When you distribute the nodes locally, but also have far fewer nodes that participate in the ledger, performance is faster.

Better Scalability⁴⁾:

Being able to add nodes and services on demand can provide a great advantage to the enterprise.

Compliance Support⁵⁾:

As an enterprise, you would likely have compliance requirements to adhere to; having control of your infrastructure enhances ability to satisfy this requirement more seamlessly.

Consensus More Efficient (fewer nodes)⁶⁾:

Enterprise or private blockchains have fewer nodes and usually a different consensus algorithm, such as BFT vs PoW.

¹⁾
“Public, Private, Permissioned [blkchn](#) Compared”, Shobhit Seth, Investopedia, 10 April 2018,
<https://www.investopedia.com/news/public-private-permissioned-blockchains-compared/>

2) 3) 4) 5) 6)
, , , , ,

“Public Vs Private Blockchain In A Nutshell”, Demiro Massessi, 12 December 2018,
<https://medium.com/coinmonks/public-vs-private-blockchain-in-a-nutshell-c9fe284fa39f>

From:
<https://www.omgwiki.org/dido/> - **DIDO Wiki**

Permanent link:
https://www.omgwiki.org/dido/doku.php?id=dido:public:ra:1.2_views:3_taxonomic:2_network_access_ctrl:private&rev=1617029272

Last update: **2021/03/29 10:47**

