

2.3.4.9 Error Taxonomy

[Return to Data Taxonomy](#)

Overview

[Return to Top](#)

There are all kinds of errors that can occur in Systems and Applications. Some errors are more or less static in nature and must be addressed before the software can be released. Others can occur during the running of the System or Application. Some of these errors are the result of aborent use of resources such as **Out of Memory** or **Dividion by Zero** while others are the result the code not doing what it is intended auch as **Invalid Data**.

- [Syntax Errors](#)
- [Runtime Errors](#)
- [Logic Errors](#)

Syntax Errors

[Return to Top](#)

A **Syntax Errors** are errors in program or script [Source Code](#) not meeting (following), or deviating from the standardized [Syntax](#) associated with the [Programming Language](#).

Syntax Errors are generally small grammatical mistakes in the Source Code and can seem as trivial as a single character (i.e., a missing semicolon, or quotations, parenthesis, braces, or brackets not balanced). In the C++ code below, there is a Syntax Error on each line. The errors are indicated by comments on the line:

```
#include <iostream>
using namespace std;

void main()
{ int x = 10                // semicolon missed
  int y = 15.4;             // Asigning an int with a floating point
number                      // Using a quotation mark instead of an
  char delimiter = ",";     // Using a quotation mark instead of an
apostrophy for a character
  string myText = 'hello World'; // Using apostrophe instead of a quotation
Mark
  cout << " "<< meText;      // referencing a variable that is not
```

```
declared  
} } // Too many closing braces
```

Some software [Integrated Development Environments \(IDEs\)](#) check [Source Code](#) for [Syntax Errors](#) in real-time, while others only generate syntax errors when a program is compiled. Even if a source code file contains one small syntax error, it will prevent an application from being successfully compiled and deployed. Similarly, if you run a script through an interpreter, any **Syntax Errors** will prevent the script from completing. In most cases, the compiler or interpreter provides the location (or line number) of the **Syntax Error**, making it easy for the programmer to find and fix the error.

As a general rule, [Strongly Typed Languages](#) create more **Syntax Errors** than [Weakly Typed Languages](#) with the idea that these **Syntax Errors** help prevent harder to diagnose [Runtime Errors](#) or [Logic Errors](#).

DIDO Specifics

[Return to Top](#)

Solidity Syntax errors are detected within [Syntax Highlighting](#) the [remix](#) or other [Integrated Development Environments \(IDEs\)](#) such as [Microsoft: Visual Studio Code \(VS Code\)](#) with the Solidity [Plug In](#).

A very important aspect of **Syntax Errors** caught within the IDE is that these errors are NOT caught on the blockchain, but rather just inside the IDE. This means there is no expenditure of Gas to catch these errors.

Runtime Errors

[Return to Top](#)

[Runtime Errors](#) refer to a class of errors occurring during the execution of a program or an [Application](#). Runtime errors imply [Bugs](#) in the running code developers expected but were unable to correct. For example, when the Application can not allocate more memory, an **Out of Memory** is triggered, terminating the Application and resulting in a [Core Dump](#). The Core Dump and a [Debugger](#) are some of the most powerful and useful tools in tracking down **Runtime Errors**.

Table 1: A common list of errors adapted from <https://www.techslang.com/definition/what-is-a-runtime-error/>

Error Name	Description
Memory Leak	Memory leaks happen when a program drains your computer's Dynamic Random Access Memory (DRAM) . It often arises from unpatched software, such as when you fail to update the Operating System (OS) to the newest release.

Error Name	Description
Out of Memory	Out of Memory is an error when there is no longer any spare memory to allocate to programs, or the memory requested exceeds the amount of memory available. An Out of Memory error causes programs to terminate or even the entire computer to crash triggering a Core Dump. The Out of Memory occurs when • A computer has a small amount of Random Access Memory (RAM) • Too many Applications or hardware pieces running at once • A request is made for a large amount of Random Access Memory (RAM) that exceeds amount available Note: Deleting items from the hard drive does not alleviate this problem
Heap Error	A Heap Error is when code inadvertently overwrites control information memory management functions use to control heap usage. The application that you are debugging must have been built with the heap check capability.
Out of Stack Space	The Stack Memory is the working area of memory that grows and shrinks dynamically with the demands of your executing program. Whenever an Application, program, function, procedure or a declarative block is invoked, or a local Variable is created, memory is allocated from the Stack. Some common reasons for this error are: • There are too many active procedure call being made (i.e., functions, procedures, methods, etc.) • There is a request to allocate local variables that exceed the available stack space • There are too many fixed-length strings, which in most compilers is allocated from the Stack • There is a Recursion issue
Division by Zero Error	Division by Zero (DIV/0) can occur in any application where the quotient is a Variable value substituted at Run Time. It is an error typically associated with spreadsheets. When formula inputs in the spreadsheet are left blank, the total might display a DIV/0 error. The cell formulas need to be formatted in a precise manner to produce the correct output.
Encoding Error	Encoding errors happen when you're rendering a file, say a video file, to convert it into a usable or accessible file format. This is due to the resource-intensive nature of the encoding process. Error messages linked to this type of error include "encoding overloaded" or "encoding failed."
Input/Output Device Error	Input/Output (I/O) device errors occur when issues arise with the read/write function of a device. Common causes include device malfunction, outdated drivers, OS incompatibility, and faulty universal serial bus (USB) ports. As a result, users would get a prompt saying that the device wasn't accessible, making it impossible to transfer or encode files into it. Usually, the memory drive or the computer only needs to be restarted to get rid of the issue.
Overflow Error	Overflow Error occurs when an attempt is made to place a value into memory an integer (whole number) that is too large for the integer data type in a given system. For example, putting a 32-Bit value into a 16-Bit data field). Also see: Wrap Around

Error Name	Description
Range Error	A Range Error occurs when a value is not in the set or range of allowed values. For example, a percent might only allow numbers between 0 and 100, and an attempt is made to store a -1 or 101 into the field.
Segmentation Fault	Segmentation Fault (SEGFault) is an error returned by Hardware (H/W) with memory protection that tells the Operating System (OS) that a memory access violation has occurred.
Undefined Object Error	An undefined object error happens when a program attempts to call a function for a PHP or JavaScript object (or a C++ variable) that isn't defined or assigned a value. The error also occurs for deeply nested objects. In simpler terms, the code "cannot read" or find where a property is because it does not exist or is buried several levels deep within the code.
Underflow	An Underflow Error occurs when a mathematical operation results in a number which is smaller than what the device is capable of storing. For example, an negative number being put into an unsigned number space. Also see: Wrap Around .
User Defined Exception	User Defined Exception occurs is part of the architecture and design of an Application , routine, methd or object.

There are always costs associated with **Runtime Errors** and many of these errors can be traced to poor specification of requirements, misunderstanding of what the requirements are, or ignorance of the requirements.

Many studies have shown that requirements errors are very costly. By one estimate (in an article by Donald Firesmith for the Software Engineering Institute), requirements errors cost US businesses more than \$30 billion per year and often result in failed or abandoned projects and damaged careers. The common wisdom is to find and fix requirements errors early in the lifecycle of a project, but that is easier said than done. Furthermore, the actual cost of a requirement error has been hard to quantify in the past. This resulted in a "business-as-usual" approach rather than proactively creating programs to find these errors early¹⁾.

There are some important tools, processes and resources available to help prevent some Runtime Errors before the code is even executed.

- [Static Code Analysis](#) using [Code Review Tools](#)
- Have a [Requirement Traceability](#) plan
- Following the guidance provided in the Non-Functional Requirements section on [Modifiability](#)
- Understanding and using the [Common Weakness Enumeration \(CWE\)](#)
- Conducting [Peer Reviews](#)
- Establish a [Case Management](#) process with [Automated Bug and Issue Tracking](#) tools such as [Jira \(Bug tracking system\)](#) or Bugzilla
- Make sure there are clean compiles with no errors, warnings or informational messages
- Conducting in-depth, detailed testing covering requirement conformity checks outlined in [4.3.3.5 Testability](#), including:
 1. [Unit Testing](#)
 2. [Integration Testing](#)
 3. [End-to-End Testing \(E2E Testing\)](#)

4. [Smoke Testing](#)
5. [Sanity Testing](#)
6. [Regression Testing](#)
7. [Acceptance Testing](#)
8. [White Box Testing](#)
9. [Black Box Testing](#)
10. [Interface Testing](#)
11. [Interoperability Testing](#)

DIDO Specifics

[Return to Top](#)

Runtime errors occur only after the Smart Contract Code has been compiled to a byte code, deployed to the blockchain and executed on the EVM. These runtime errors occur when Ethereum “thinks” that there is something wrong with the Smart Contract. If the Runtime error occurs during a Transaction, any State Changes made during the Transaction are canceled and the Transaction is reverted. Depending on the kind of error, all or some of the gas in the Transaction is consumed, or a portion is returned. Runtime errors are harder to troubleshoot than Syntax errors because the Solidity Compiler can not help with the diagnostics.

Runtime Errors are more serious than Syntax Errors since the contract has already been deployed to the blockchain, and it is not possible to just update the code by redeploying it.

Out of Gas	The out of gas error occurs when all the gas allotted for the transaction is consumed before the transaction could complete.
Revert	The revert error occurs when a transaction is terminated in the Smart Contract by a Revert statement. See: revert
Invalid OpCode	1. assert() uses the 0xfe opcode to cause an error condition 2. require() uses the 0xfd opcode to cause an error condition Note: neither 0xfe nor the 0xfd opcodes in the yellow paper, you won't find them. This is why you see the invalid opcode error, because there's no specification for how a client should handle them.
Invalid Jump	Invalid-Jump is an old error replaced by revert . However, it still occurs when older published contracts (Solidity versions prior to 0.4. 10) are used. The EVM calls a jump opcode with an invalid-jump destination. Note: This is caused by malformed inputs, usually during contract creation.
Stack Overflow	
Stack Underflow	

Logic Errors

[Return to Top](#)

Logic Errors occur when there is a fault in the logic expressed by the [Software \(SW\)](#) or when the

(i.e., **if-then** statements) through the SW creates a situation which is wrong or incorrect. The chance of a **Logic Error**, increases with the number of **Decision Points** found with the SW code.

Logic Errors can originate anywhere in the **System Lifecycle** from its conception to its execution.

Sometimes **Logic Errors** are reported as a **Bug**, however, not all “Bugs” are discovered or reported. Logic errors resulting in a **Crash** are generally quite obvious and are generally reported. However, Bugs which do not result in a crash but can only be found with a detailed forensic analysis of the **Datstores** are some of the hardest to discover and even track down.

Sometimes a **Logic Error** is introduced when a developer misinterprets the requirements or inadvertently implements the boolean calculus used in the **Control Flow operations**. Some examples:

- Assuming that memory is **null**ed before it is used
- Incorrectly specifying the logical comparison operators (i.e., <, <=, ==, ==, !=, >, or >=). For example, specifying a numerical check for a percent and specifying **p >= 0 && p < 100** instead of **p >= 0 && p <= 100**
- Incorrectly using the equivalent operators (i.e., ==, ===). == converts the variable values to the same type before performing comparison. This is called **Type Coercion**. === does not do any type conversion (coercion) and returns true only if both values and types are identical for the two variables being compared.
- Incorrectly using the assignment operator, =, instead of the comparison operator, ==
- Assuming that indexing arrays at one
- Incorrect incrementing a pointer instead of the value stored at the pointer
- Assuming a string is terminated by a **null**
- Comparing an empty string, "" to a **null** string

Sometimes, a **Logic Error** is a **Bug** because it introduces a **Weakness** making the System or Application **Vulnerable** for malicious **Exploitation**. These kinds of “Bugs” could exist for a long time (i.e., years) before they are actually exploited.

Software (SW), **Firmware**, and **Hardware (H/W)** weakness types that have security ramifications are also potential **Logic Errors**. These Weaknesses can be flaws, faults, Bugs, or other errors in Software, Firmware, or Hardware and could have been introduced during any phase of the **System Lifecycle** from conceptualization, requirements specifications, architecture, code, or implementation.

Currently, there are 900+ Weaknesses defined by the **Common Weakness Enumeration (CWE)** most of which can be found through **Static Code Analysis** and **Testing**

DIDO Specifics

[Return to Top](#)

Logic Errors occur once the [Smart Contract](#) is deployed and it occurs because there is a problem with the logic of the Smart Contract. An important difference between a Solidity **Runtime Error** and a **Logic Error** is that the [Ethereum Virtual Machine \(EVM\)](#) does not consider it to be an error and the EVM assumes the Smart Contract is executing as expected. **Logic Errors** are either dangerous or produce false or erroneous results. For example, The [Reentrancy Attack](#) of a [Decentralized Autonomous Organization \(DAO\)](#) called [The DAO Project](#) had a Smart Contract attack 2016. The attack was a **Logic Error** and not a **Runtime Error**, a **Syntax Error** or a problem with the EVM.

Logic Errors are the hardest to fix because there are no tools that can examine a Smart Contract and find the Logic Errors. There are efforts underway at Ethereum called the [Ethereum Formal Verification](#).

DIDO Specifics

[Return to Top](#)

This section is an overview of how to find and fix bugs in general.

	Solidity Compiler	Solidity Debugger	Solidity Linter	Tests
Syntax Errors	X		X	
Runtime Errors		X		X
Logic Errors		X	X	X

¹⁾

Joe Marasco, Stickyminds, [What Is the Cost of a Requirement Error?](#), 26 June 2007, Accessed 27 January 2022, <https://www.stickyminds.com/article/what-cost-requirement-error>

From:
<https://www.omgwiki.org/dido/> - **DIDO Wiki**

Permanent link:
https://www.omgwiki.org/dido/doku.php?id=dido:public:ra:1.2_views:3_taxonomic:4_data_tax:10_errors:start&rev=1643911204

Last update: **2022/02/03 13:00**

