

4.2.1.4 Network Platforms

[Return to Platforms](#)

A DIDO, by definition, is a collection of [networked nodes](#). Traditionally, the network is assumed to be [Ethernet](#) with nodes connected over [Local Area Network \(LAN\)](#) and/or a [Wide Area Network \(WAN\)](#) using a [Network Device](#).

The connections can either be:

- [Wired Network](#) using
 - [Network Cabling](#)
 - [Universal Serial Bus \(USB\)](#)
- 2. [Wireless Network](#) using [Wireless Fidelity \(Wi-Fi\)](#)

Note: for Private, permissioned DIDOs, there may be explicit bans on wireless or even USB connections.

However, there is a lot of growth and development using other wireless connections other than Ethernet or USB. For example:

- [Bluetooth](#)
- [ZigBee](#)
- [Near-Field-Communication \(NFC\)](#)

Consequently, it is important to identify the kinds of connections that are required to support the DIDO. Some example are:

- Many contactless payments systems use [Radio Frequency Identification \(RFID\)](#) and NFC
- Many supply chains use RFID
- Many smart home efforts use WiFi and zigbee
- Many automobiles use Bluetooth to connect phones, make queries, play music, etc.

From:

<https://www.omgwiki.org/dido/> - **DIDO Wiki**

Permanent link:

https://www.omgwiki.org/dido/doku.php?id=dido:public:ra:1.4_req:1_func:platform:net_arch&rev=1616682208

Last update: **2021/03/25 10:23**

