

Bytecode

[Return to Glossary](#)

Bytecode is computer object code that is processed by a program, usually referred to as a [Virtual Machine \(VM\)](#), rather than by the “real” computer machine, the hardware processor. The VM converts each generalized machine instruction into a specific machine instruction or instructions that this computer's processor will understand. **Bytecode** is the result of compiling source code written in a language that supports this approach. Most computer languages, such as C and C++, require a separate compiler for each computer platform - that is, for each computer operating system and the hardware set of instructions that it is built on. Windows and the Intel line of microprocessor architectures are one platform; Apple and the PowerPC processors are another. Using a language that comes with a VM for each platform, your source language statements need to be compiled only once and will then run on any platform.

The best-known language today that uses the **Bytecode** and VM approach is Java. The LISP language, used in artificial intelligence applications, is an earlier language that compiled **Bytecode**. Other languages that use **Bytecode** or a similar approach include Icon and Prolog.

Source: <https://whatis.techtarget.com/definition/bytecode>

From:
<https://www.omgwiki.org/dido/> - **DIDO Wiki**

Permanent link:
https://www.omgwiki.org/dido/doku.php?id=dido:public:ra:xapend:xapend.a_glossary:b:bytecode&rev=1636045072

Last update: **2021/11/04 12:57**

