

Hashgraph

[Return to Glossary](#)

Hashgraph is a [Distributed Ledger Technology \(DLT\)](#) that has been described as an alternative to [Blockchains](#). The Hashgraph technology is currently patented, and the only authorized ledger is Hedera Hashgraph. The native cryptocurrency of the Hedera Hashgraph system is **HBAR**.

Unlike blockchains, Hashgraphs do not use [Miner Nodes](#) to validate [Transactions](#). Instead, Hashgraph use a "[gossip about gossip](#)" protocol where the individual [Nodes](#) on the network "gossip" about transactions to create [Directed Acyclic Graphs \(DAGs\)](#) that time-sequence transactions without bundling them into blocks. Each "gossip" message contains one or more transactions plus a timestamp, a digital signature, and cryptographic hashes of two earlier events. This makes Hashgraph form an asynchronous Byzantine Fault-Tolerant (aBFT) consensus algorithm.

Hashgraph was invented in the mid-2010s by the American computer scientist Leemon Baird. Baird is the co-founder and chief technical officer of Swirlds, a company that holds patents covering the Hashgraph algorithm.

Source: <https://en.wikipedia.org/wiki/Hashgraph>

From:

<https://www.omgwiki.org/dido/> - **DIDO Wiki**

Permanent link:

https://www.omgwiki.org/dido/doku.php?id=dido:public:ra:xapend:xapend.a_glossary:h:hashgraph&rev=1641866581

Last update: **2022/01/10 21:03**

