

2.2.6 DEFINE CONTAINER Command

[Return to DidoDLL](#)

Purpose

[Return to Top](#)

Syntax

[Return to Top](#)

```
DEFINE CONTAINER <ContainerName> AS
  IMAGE      = <ImageName>
  COMMAND    = <ShellCommand>
  ARGUMENTS  = <ArgumentListText>
```

Where

[Return to Top](#)

- **ContainerName**
- **ImageName**
- **ShellCommand**
- **ArgumentListText**

Examples

[Return to Top](#)

[| Examples of Defining Container in DidoLL](#)

```
DEFINE CONTAINER PeerDiscovery AS
  image      = PeerDiscovery
  command    = ["/bin/sh", "-c"]
  arguments  = "set -e -x; while true; do python
/etc/peer_discovery.py; "
              "sleep 15; done";
```

```
DEFINE CONTAINER fullNode AS
  image      = fullNode
  command    = ["/bin/sh", "-c"]
  arguments  = "set -e -x; while true; do python
/etcd/peer_discovery.py; "
              "sleep 15; done"
```

From:
<https://www.omgwiki.org/dido/> - **DIDO Wiki**

Permanent link:
https://www.omgwiki.org/dido/doku.php?id=dido:public:s_cli:05_contents:01_prt:04_dll:appcontainer&rev=1619888164

Last update: **2021/05/01 12:56**

