

2.4.1 DEFINE CONSTANT Command

[Return to DidoDLL](#)

Purpose

[Return to Top](#)

A **Constant** is a symbolic name that captures a value does not change while a program is running and is usually used for capturing initialization or site specific parameters. Constants are in contrast with variables, which are symbols represent different values that can change during the execution of program.

A constant can be a:

- **number** such as 25, 3.6, 3.14, etc.
- **character** such as the character 'a', '\$', '_', etc.
- **text string** such as "Bitcoin", "Hyperledger", "Medical Records", etc.

Syntax

[Return to Top](#)

```
DEFINE CONSTANT <ConstantName> AS <SimpleExpression>;
```

Where

[Return to Top](#)

- **ConstantName** ::= textual name associated with the Constant
- **SimpleExpression** ::= NumericConstant | CharacterConstant | StringConstant

Examples

[Return to Top](#)

[| Examples of Defining Constants in DidoLL](#)

```
DEFINE CONSTANT PRECISION      AS 2
DEFINE CONSTANT Version         AS 3.5.1
```

```
DEFINE CONSTANT Currency_Symbol AS '$'  
DEFINE CONSTANT Currency_Name   AS "My Coin"
```

From:
<https://www.omgwiki.org/dido/> - **DIDO Wiki**

Permanent link:
https://www.omgwiki.org/dido/doku.php?id=dido:public:s_cli:05_contents:01_prt:06_dddl:constant&rev=1619919010

Last update: **2021/05/01 21:30**

